CRANE SCALES

100g to 1ton

(0.5, 1 ton)

STANDARD CRANE SCALES (CCS)

Features:

- Rugged aluminum diecast enclosure.
- 25 mm height LED display
- Maximum safety overload 200%.
- Inbuilt sealed maintenance free re-chargeable battery and battery charger (Optional)
- RF keyboard, operating distance 20mtr. (optional)
- RS-232 Interface (Optional)
- Multiple print options with Sr. No, Date, Time & Weight in horizontal / vertical mode.
- Date & Time entry facility.
- Multiple weighing units.
- Storage of weights in memory upto 100 samples.
- Power saving by switching off the display.
- · Automatic zero tracking.
- Software linearity correction.
- · Display hold facility.
- Gross & Net Weight function.




Common Specifications:

MODELS	CAPACITY	ACCURACY	NET WT. (Kg)
CCS-500K100	500Kg	100g	4.2
CCS-1T200	1000Kg	200g	4.2

Taring Range : Up to full capacity

Response time: 5 seconds

Power Req: 90-250V, 50/60Hz, 10 Watt Operating Temperature: 10 to 45 deg C



All Specifications and designs are subject to change for improvement.



301, Punit Indl. Premises, Turbhe Naka, Navi Mumbai - 400 705.

Tel.:+91 22 6139 3000 (100 lines) E-mail: sales@contechindia.in Website: www.contechindia.com



Plot No. EL-221 TTC Indl. Area, MIDC (Electronic Zone), Mhape, Navi Mumbai - 400 710.