## CRANE SCALES

(30, 40, 50 ton)

## **STANDARD CRANE SCALES (CCS)**

## Features :


- Steel heavy duty enclosure.
- 38mm height LED display.
- Maximum safety overload 200%.
- Inbuilt sealed maintenance free re-chargeable battery and battery charger (Optional)
- RF keyboard, operating distance 20mtr. (optional)
- RS-232 Interface (Optional)
- Multiple print options with Sr. No, Date, Time & Weight in horizontal / vertical mode.
- Date & Time entry facility.
- Multiple weighing units.
- Storage of weights in memory upto 100 samples.
- Power saving by switching off the display.
- Automatic zero tracking.
- Software linearity correction.
- Display hold facility.
- Gross & Net Weight function.



Commor	ı Specif	ications :	

MODELS	CAPACITY	ACCURACY	Y DIMENSION				EXF	NET WI.
			Н	A	В	С		(Kg)
CCS-30T10K	30 ton	10Kg	1110	160	260	90	500x310	156
CCS-40T20K	40 ton	20Kg	1200	180	220	110	440x410	235
CCS-50T20K	50 ton	20Kg	1310	200	270	110	440X410	280

Taring Range : Up to full capacity Response time : 5 seconds Power Req : 90-250V, 50/60Hz, 10 Watt Operating Temperature : 10 to 45 deg C



All Specifications and designs are subject to change for improvement.



301, Punit Indl. Premises, Turbhe Naka, Navi Mumbai - 400 705.
Tel. :+91 22 6139 3000 (100 lines)
Fax :+91 22 2761 8421
E-mail : info@contechindia.in / sales@contechindia.in
Website: www.contechindia.com

